

*This matrix provides the necessary information to create the desired VarCOM capacitor control part number*

example: **VCC 950 1 4R N N XX**

**CODE FEATURES**

950P	Time and Voltage Override with Pager
1600	Time, Temperature, Voltage Override, Multiple Schedules and Logging with ComFlex Communications Ready
2600	VAR, Time, Temperature, Voltage Override, Multiple Schedules, Logging and ComFlex™ Communications Ready (Line Current Sensor Required)

**CODE INPUT POWER**

1	120 VAC 60Hz
2	240 VAC 60Hz
3	220 VAC 50Hz
4	120 VAC 50Hz
5	127 VAC 60Hz

**CODE MOUNTING**

4R	4 Stab Meter Base with Mounting Ring
4S	4 Stab Meter Base Ringless
6R	6 Stab Meter Base with Mounting Ring
6S	6 Stab Meter Base Ringless
P	Pole Bracket Mounted with Terminal Strip-Specify Hole
PA	Pole Mounted with Amphenol Connector

**CODE NEUTRAL SENSING**

N	No Neutral Sensing
T	Neutral Sensing with Terminal Strip Sensor Connections
B	Neutral Sensing with 6 Stab Meter Base

**CODE NEUTRAL CURRENT SENSOR**

H	HD Electric Current Sensor
O	Other Current Sensor
NH	No Sensor, Compatible with HD Electric
NO	No Sensor, Compatible with Other
N	No Sensor Required

**CODE ComFlex™ COMMUNICATIONS**

Contact HD Electric for Communications Options